



# MOTORIZED RETRACTABLE MONITOR



Display  
Size 17.3"



Single-wire  
Connectivity



Centralised  
Control

## Chairman Unit

- . Advanced and stable "IRIN" chip and DSP/DDOV Digital Conference technology to realize digital signal transmission and processing.
- . Dual backup design, supports Loop in-Loop-out and phantom power supply simultaneously with dual system audio signal output at the same time, enhancing audio signal.
- . Material: Zinc-aluminium alloy microphone stem, with built-in 9.7mm high-fidelity goldplated capacitive pickup head accurately calculate the aperture and spacing which improve the human voice frequency response range pickup sensitivity.
- . Unique cavity and integrated shape sound picking steel mesh design, accurately controls the sound picking Angle, avoiding acoustic feedback and howling.
- . High sensitivity sound pickup design with built-in automatic gain AGC function, digital equalization EQ, environmental noise elimination AEC with effective sound pickup distance up to 50-60cm.
- . All-zinc aluminium alloy panel embedded with touch glass panel having 6 Mohs hardness makes it waterproof and dustproof.
- . Nano-level fingerprint isolation technology with oleophobic waterproof layer effectively isolate water, oil and stains ensuring clean surface having anti-fingerprint & anti-sweat effect.
- . Equipped with 3.5" HD LCD touch screen with options displaying user LOGO, participant nformation, speaking time, conference services, calendar and checking voting data etc.
- . ime function supports dynamic display of speaking time allowing user to set the countdown and time of speaking.
- . High fidelity lossless audio transmission technology with 48KHz audio sampling frequency. It ensures sensitive pickup with clear speech having frequency response up to 30Hz-20KHz.
- . Microphone length of 90mm with speech indicator light. The colour is displayed as per the status and identity.
- . Three colour indicator display: Red-Normal, Green-VIP, Yellow-Numbered units.

- . Microphone joints and all connectors are made of pure copper for better sound quality with stability and voice pickup distance.
- . High quality of elastic shrinkage sponge cover, good air permeability, prevents it from fall and deformation providing a long life.
- . Intelligent audio detection function senses the distance between two adjacent units and if its close with audio automatic anti-phase attenuation it eliminates whistling.
- . Daisy Chain connection with professional 8-core or CAT5 cable wire adopts full line aluminium foil, waterline shielding, effectively avoids and prevent line electromagnetic interference.
- . Built-in multi-channel internal communication and conference service function, support to send tea, paper, pen, waiter and other demand notification, support Web page service screen to process the request service.
- . The digital ID addressing method is used to customize the unit number with a Unique ID which avoid conflicts.
- . Look-At-Me built-in which controls the camera to track the active speaker.
- . Supports Multi multi-camera tracking in the same conference unit.
- . The chairman unit has the function of controlling the order of the meeting and having the priority to speak, and can close other representative units that are speaking.
- . Any chairman or representative unit can be set as a VIP unit, and there is no restriction on the speech of VIP units. The maximum number of VIP units can be set is 150.
- . Super anti-interference feature effectively eliminates the signal interference of mobile phone, radio wave, Bluetooth, WiFi etc.
- . Equipped with a 3.5mm headphone interface, it can be used as a meeting monitoring for participants, and the volume can be adjusted freely.
- . Equipped with one SD card interface which supports to import files and also for the upgrade.



## Delegate Unit

- 17.3" HD touch screen, aluminum alloy embedded with toughened glass, IPS full-view display.
- Support 1920 x 1080 HD display, with 10-point capacitive touch and backlight adjustment function (support customized 4K resolution).
- Decentralized design so no system server is required. The Chairman and Secretary can push content to all screens just by pressing one button and can control display elevation.
- With the Chairman, Secretary, and Delegates three kinds of identity permissions can be programmed.
- Loop-in Loop-out connection on network cable, it can support and control 42 displays simultaneously.
- Ultra-thin touch HD screen and elevator is aesthetically designed hiding all cables, connectors, and seamless body with no screws exposed.
- Touch screen has automatic power supply mode and gets on when it comes and shuts down when goes in cover.
- Compatible with a variety of Windows system operations it consists of a Mini Computer that works on low power consumption, is quick in operation, and with full function.
- Multi-point balanced lifting control system with a double silent sliding rail structure is designed for smooth& uniform lifting.
- Digital intelligent synchronous positioning recognition processing technology ensures accurate positioning, unified speed, and free lifting of the lifting system.
- High-quality aluminum structure and CNC engraving, the screen thickness is less than 7mm giving an overall aesthetic look.
- Easy to transport as the panel comes with just 3mm thickness and 70mm width also results in less pressure on the table.

- Highly durable Military-Grade panel keys without compromising on the sensitivity of the keys.
- Equipped with a computer switch shortcut button to support manual switch, protecting the equipment from data loss and damage.
- The outer surface comes with anodic oxidation treatment in bright color, sandblasting, and wire drawing as per industry standards of corrosion resistance.

## Technical Specifications

Model	Chairman - CRM17 Delegate - DRM17
Power Consumption	40W
Front Screen Size	17.3"
Rear Screen Size	10.1"
Video Interface	HDMI, VGA Interface
Lift Control	Manual Control, Remote Control, Software, Grouping, Central Control RS-232/485 Control
Control Interface	Dual RJ45, Switch Machine, Data Transmission Interface
Material	All Aluminium Alloy
Craft	CNC Carved, Anodized

**AVAILABLE THROUGH PAN INDIA DISTRIBUTOR & DEALER NETWORK**

